

# powermode

## Uninterruptible Power Supply

BBONE 2400VA

BBONE 1200VA



**BBONE-024S**

**BBONE-012S**

### Features

- Simulated sine wave inverter
- Wide input voltage range
- 10 A or 20 A standard AC charging current
- LCD display for comprehensive information
- Overload, short circuit and reverse polarity protection

MODEL	BBONE-012S	BBONE-024S
CAPACITY	1200VA/ 720W	2400VA/ 1440W
INPUT		
Voltage	230 VAC	
Acceptable Voltage Range	90-280 VAC	
Frequency	50 Hz/60 Hz (Auto sensing)	
OUTPUT		
AC Voltage Regulation (Batt. Mode)	± 10%	
Efficiency (Peak)	82%	85%
Transfer Time	20 ms typical	
Waveform (Batt. Mode)	Simulated sine wave	
BATTERY		
Battery Type and Numbers	12 V 100Ah x 1	12 V 100Ah x 2
PROTECTION		
Full Protection	Overload, short circuit and polarity reserve protection	
PHYSICAL		
Dimension, D X W X H (mm)	392 x 250 x 450	345 x 400 x 450
Net Weight (kgs)	40.5	75.8
OPERATING ENVIRONMENT		
Humidity	0 to 90% Relative Humidity(Non-condensing)	
Operating Temperature	0°C to 40°C	
Storage Temperature	-15°C to 50°C	

\* Product specifications are subject to change without further notice

E. & O.E.