



LiFePO₄ Battery Range

FW 12-7.5

Electrical Characteristics

Nominal Voltage[V]	12.8V
Nominal Capacity	7.5AH
Energy	96Wh
Internal Resistance	≤60mΩ
Cycle Life	>2000 cycles at 0.2C 100% DOD
Months Self Discharge	<3%
Efficiency of Charge	100% at 0.5C
Efficiency of Discharge	96~99% at 1C

Charge

Charge Volt	14V-14.6V
Charge Mode	CC at 0.2C to 14.6V, then at CV14.6V to charge current less than 0.02C
Charge Current	1.5A
Max. Charge Current	7.5A
Charge Cut-off Voltage	15.6V+/-0.2V

Discharge

Max. Continuous Current	7.5A
Max. Pulse Current	15A(<3s)
Discharge Cut-off Voltage	8V

Environment

Charge Temperature	0°C to 45°C (32F to 113F) at 60±25% Relative Humidity
Discharge Temperature	-20°C to 60°C (-4F to 140F) at 60±25% Relative Humidity
Storage Temperature	0°C to 40°C (32F to 104F) 60±25% Relative Humidity
Water Dust Resistance	IP56

Mechanical

Cell Material	LiFePO ₄
Plastic Case	ABS
Dimensions(mm)	150x65x101 mm
Weight (kg)	1kg
Terminal	T2

BMS

Protection Function	Over charge protection, Over discharge protection, Over current protection, Short current protection, Balanced function, Temperature protection
---------------------	---